



General Purpose Handheld Linear Imager Bar Code Reader with Datalogic's STAR Cordless System™

The QuickScan reader series is Datalogic Scanning's value line of general purpose handheld data collection products. The QuickScan Mobile QM2100 handheld reader is the perfect entry level cordless solution for general purpose data collection applications.

For small to mid-size business owners, the freedom of dependable wireless devices has been priced out of reach due to features and functionality that are just not necessary for basic data collection tasks. For simple point-to-point connectivity (single reader to single base station), the QuickScan Mobile reader offers security and reliability with Datalogic's STAR Cordless System. It's fast, easy to use and guaranteed Wi-Fi interference free.

Outstanding bar code reading performance and reliability make the QuickScan Mobile reader ideal for use at the point of sale, plus this multi-purpose device can also double

for inventory, price checking and shelf replenishment activities. A 12 m / 40 ft radio range provides a wide working area and eliminates the restraints caused by cabled devices, providing a safer and more efficient work environment.

The QM2100's cradle provides hands-free reading capabilities and a scan-while-charging feature ensures constant up-time for increased productivity. Datalogic's patented Batch Mode combined with a long lasting lithium-ion battery allows for reliable data collection when out-of-range from the base station.

Standard multi-interface capabilities (QM2130) provide host connectivity via USB, RS-232, Keyboard Wedge and Wand Emulation while IBM interface models (QM2110) provide connectivity via IBM46XX, USB and RS-232 emulation. Convenient Plug & Scan kits provide for easy installation and include everything required to get up and running quickly.



Features

- Multi-purpose device for inventory, price checking and shelf replenishment activities
- 100% Compatible with Datalogic STAR Cordless System™
- Radio range (open air) 12 m / 40 ft for point-to-point connectivity
- Radio frequencies available in 433 MHz or 910 MHz
- User replaceable lithium-ion battery
- Scan-while-charging capability
- Latch mechanism secures reader in cradle providing stable mobility for use on carts
- Batch mode capability
- Multi-interface: USB, RS-232, Keyboard Wedge and Wand Emulation
- Supports GS1 DataBar™ linear codes



Specifications

CORDLESS COMMUNICATIONS

DATALOGIC STAR CORDLESS SYSTEM™

Effective Radiated Power: 433.92 MHz: < 10 mW
910 MHz: < 1 mW
Point-to-Point Configuration
Radio Frequency: 433.92 MHz; 910 MHz
Radio Range (Open Air): 12.0 m / 40.0 ft

DECODING CAPABILITY

1D / LINEAR CODES

Autodiscriminates all standard 1D codes including GS1 Databar™ linear codes

ELECTRICAL

BATTERY

Battery Type: Lithium-Ion, 700 mAh
Charge Time: External Power: 6 Hours
Reads per Charge: 20,000
Battery Charging (Red); Charge Completed (Green); Power/Data (Yellow)
Operating (Typical): Charging: 4 W
5 +/- 5% VDC

CRADLE INDICATOR LEDS

CURRENT

INPUT VOLTAGE

ENVIRONMENTAL

AMBIENT LIGHT

DROP RESISTANCE

ESD PROTECTION (AIR DISCHARGE)

HUMIDITY (NON-CONDENSING)

PARTICULATE AND WATER SEALING

TEMPERATURE

0 - 100,000 lux
Withstands repeated drops from 1.5 m / 4.9 ft onto a concrete surface
15 kV
0 to 90%
IP30
Operating: 0 to 40 °C / 32 to 104 °F
Storage/Transport: -20 to 70 °C / -4 to 158 °F

INTERFACES

RS-232 / USB / Keyboard Wedge / Wand Multi-Interface

PHYSICAL CHARACTERISTICS

COLORS AVAILABLE

DIMENSIONS

WEIGHT

Black; White
Cradle: 8.0 x 13.0 x 9.0 cm / 3.1 x 5.1 x 3.5 in
Reader: 17.1 x 9.0 x 6.8 cm / 6.7 x 3.5 x 2.7 in
Cradle: 181.0 g / 6.4 oz
Reader: 189.0 g / 6.7 oz (Without Batteries)

READING PERFORMANCE

IMAGER SENSOR

LIGHT SOURCE

PRINT CONTRAST RATIO (MINIMUM)

READ RATE (MAXIMUM)

READING ANGLE

READING INDICATORS

RESOLUTION (MAXIMUM)

CCD Solid-state 2088 pixels
Illumination: LED Array 630 - 670 nm
20%
235 reads/sec.
Pitch: 75°; Roll (Tilt): 30°; Skew (Yaw): 70°
Beeper (Adjustable Tone); Good Read LED
0.100 mm / 4 mils

READING RANGES

TYPICAL DEPTH OF FIELD

Minimum distance determined by symbol length and scan angle.
Printing resolution, contrast, and ambient light dependent.
5 mils: 3.5 to 10.5 cm / 1.4 to 4.1 in
7.5 mils: 1.5 to 13.5 cm / 0.6 to 5.3 in
10 mils: 0.5 to 17.0 cm / 0.2 to 6.6 in
13 mils: 1.0 to 21.5 cm / 0.4 to 8.4 in
20 mils: 1.0 to 27.0 cm / 0.4 to 10.5 in

SAFETY & REGULATORY

AGENCY APPROVALS

The product meets necessary safety and regulatory approvals for its intended use.

The Quick Reference Guide for this product can be referred to for a complete list of certifications.

Complies to China RoHS; Complies to EU RoHS

EN60825-1 Class 1 LED

ENVIRONMENTAL COMPLIANCE

LED CLASSIFICATION

UTILITIES

DATALOGIC ALADDIN™

Datalogic Aladdin configuration program is available for download at no charge

OPOS / JAVAPOS

JavaPOS Utilities are available for download at no charge
OPOS Utilities are available for download at no charge

WARRANTY

3 Years

© 2007-2008 Datalogic Scanning Inc.

All rights reserved. • Protected to the fullest extent under U.S. and international laws.
• Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc.

Datalogic is a registered trademark of Datalogic S.p.A. in many countries and the Datalogic logo Datalogic Aladdin, Diamond, PuzzleSolver and STAR Cordless System are trademarks of Datalogic S.p.A.

QuickScan is a registered trademark of Datalogic Scanning Inc.; Other brand and product names may be trademarks of their respective owners.

Product specifications are subject to change without notice.

DS-QUICKSCANMOBILE-ENA4 20080916

www.scanning.datalogic.com